

Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions Worldwide

AFT-4100

Single Line Analog Wall mount Phone



- Single line analog wall mount phone.
- Magnetic hook switch.
- Faceplate with customizable hotel logo.
- Coiled cord with optional bungee cord (anti-drop string).

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality,impeccable workmanship and stylish products.

At AEi your satisfaction is our priority.





AEi-Corporate Office

Carrollton, Texas , U.S.A Sales: +1.254.335.0555 sales@aeicommunications.com

AEI-EMEA Office

London, United Kindom Sales: +44 (0) 1753.643736 emea@aeicommunications.com

AEi-Asia Pacific Office

New Taipei City, Taiwan Sales: +886.2.2696.8809 asiapac@aeicommunications.com

AEi-CEE&CIS Office

Budva, Montenegro Sales: +382 69 891 251 eastern.europe@aeicommunications.com

AEi-Corporate Office

Penang, Malaysia Sales: +604.3994341 so.asia@aeicommunications.com

1. Features

Keys

Dial keys

/s (0~9, *, #)

Function keys

Mute, Volume, Release

Phone Features

- Single Line
- Ring indicator
- Mute and unmute
- One key regaining dial tone
- One key handset volume control

2. Hardware Specifications

LED Indications

· Red color ring indicator

Power

Telephone line powered

Ring Voltage

40V RMS minimum

Jacks

• RJ11 PSTN jack x 1, RJ9 Handset jack x 1

Line cord

0.7 feet x 1

Bungee cord

Coiled cord with optional bungee cord (handset anti-drop string)

Size and Weight

Dimensions:200mm(L) x82mm(W) x 52mm(H), Weight: 450g

3. Regulatory USA EU

PSTN

Part 68

TBR 21

EMI

FCC Part 15B EN55032 & EN55024

Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)

RoHS Telecom

TIA/EIA 968 compliant

Temperature

Storage: Low temperature at -10°C

High temperature at +60°C

Operating Low temperature at +5°C

High temperature at +35°C

Model: AFT-4100 AFT-4100-BC





